

Department	Standard Components	Room Tag:	1370
Room Name	Bay - ATM, 6m2	Room Code:	BATM-6-SJ
Net Room Area Briefed	6.0 M2		
No of Rooms	1		
Subtotal of Briefed Area	6.00 M2		
Hours of Operation	24 Hours		
Occupancy	N/A		
Also covers these Rooms			
Description/ Special Requirements	The Bay - ATM will provide an area for an Automatic Teller Machine which may require access to the rear of the ATM by staff or authorised personnel only. The ATM Bay may be located in close proximity to a waiting area. Provision of power and data to be according to ATM specifications. Security requirements need to be considered.		
Amendment	13.03.2014 First issue		

Room Fabric and outline specifications

ID	Fabric	Material	Finish	Specification	Selection	Remarks
5010	Ceiling	Plasterboard	Paint, washable	Flush set, suspended		
6025	Cornice	Aluminium	Powdercoat	shadow line		
9001	Doors	Solid Core	Paint	Single leaf		860mm clear opening; lockable
1000	Floor finish	Vinyl	Standard slip resistant	Seamless, coved		or floor consistent with adjacent area
2000	Skirting	Vinyl	Prefinished	Floor vinyl coved, 150 mmH		or skirting consistent with adjacent area
3000	Wall finish	Paint	Acrylic, washable			

Fixtures, Equipment and associated Services (FE)

ID	Description	Group	Qty	Ele	Data	Cd	W	H	T	N	m	W	Tap	Dns	Gas	Selection / Remarks
1540	ATM machine	3	1	yes	yes	---	---	---	---	---	---	---	---	---	---	refer to manufacturers specifications for requirements and services

Services

ID	Description	Service Category	Qty	Selection / Remarks
1006	Voice / Data outlet: double	Communications	1	ATM machine, data line, concealed
1006	Voice / Data outlet: double	Communications	1	ATM machine, telephone line, concealed
5000	Airconditioning	HVAC		
6000	General fluorescent	Lighting		
9060	GPO: Special: for equipment	Power	1	ATM machine, concealed, as specified
9020	UPS (uninterruptible power)	Power	1	ATM machine